

High Flow Rate 5:1 Dispensing Pumps

MODELS J1701056 - WITH 940MM SUCTION TUBE / J1701054 - STUBBY PUMP

This double acting air operated high-pressure pump is designed for dispensing lubricants in larger installations. Suitable for use with including multiple dispensing points with simultaneous operation. Pumps can pump all type of lubricants, even those of higher viscosity. Pumps include height adjustable bung adaptor 2" BSP (M).

FEATURES:

- Precision machined to ensure stability and long life
- Easy to operate and maintain
- Double action
- Suitable for use with oils up to 240 SAE
- Supplied with 2" adjustable bung adaptor
- Suitable for use with engine oil, synthetic oil, hydraulic oil, gear oil and automatic transmission fluid.
- Low noise level – quiet efficient and reliable

Technical Data

Ratio	5:1
Working pressure	5-8 bar (70 – 115psi)
Maximum fluid pressure	40 bar (580psi)
Air Consumption	@ 8 bar - 180 L/min
Output capacity ltr./min.	25 L/min
Suction Tube diameter mms	42 mm
Air inlet connection	¼" quick plug
Oil Delivery Connection	¾" male
Maximum Viscosity	240 SAE
<i>Test media, SAE30 oil @ 20°C through 2mtr hose length free outlet</i>	



OPTIONAL KITS AVAILABLE FOR ALL
AIR-OPERATED PUMPS