

RB Rotary Booster Pump

FUEL HANDLING EQUIPMENT – HAND OPERATED

This economical rotary pump is designed to reliably dispense various types of lubricating oils and fuels up to 75 L (20 US gal) per minute from 60 L (16 US gal) or 205 L (55 US gal) drums.

FEATURES:

- Pumps diesel, petrol, kerosene and lubricating oils up to SAE 30
- Delivers up to 75L (20 US gal) per min., or 1L (1 quart) per rotation. The 3:1 ratio gearing means that for every complete handle turn, the rotor turns 3 times.
- Rotary action allows for pumping in both directions
- Supplied with 1.8 m (6 ft) delivery hose with metal nozzle and nozzle holder
- The Rotary Booster is supplied with a three piece threaded suction tube and 2" sliding bung adaptor
- Optional 10µm VA fuel filter available separately
- 10 year parts availability



TECHNICAL DATA

Wetted components:	Aluminium, steel, plastic and nitrile rubber.
Output (PVR/H):	Up to 40 litres (10 US gal.) per min., or 1 litre (1 quart) per rotation.
Outlet Port:	25mm (1")

VA Fuel Filter

A 10 micron paper element fuel filter for use with the RB rotary pump. Inlet and outlet threads are 25mm (1") NPT (F) and fittings are included for easy installation to the RB rotary pump.

