

# Diaphragm Pumps



**FEATURES:**

- Externally serviceable air distribution system and all bolted construction
- Includes ground capability to eliminate static discharge
- Both metal and plastic bodies are available
- A variety of elastomer options including Nitrile, Viton, EPDM and PTFE are available to meet abrasion, temperature and chemical compatibility concerns
- Maximum diameter of Solid: 1/8"
- J17150601V is suitable for use with adblue and antifreeze
- Suitable for oil upto SAE250



Part number	Pump material	Membrane material	Max flow rate	Max pressure	Inlet/outlet	Air inlet
J17150600V	Aluminium	Viton	16 gpm / 60 lpm	8 bar / 115 psi	3/4"	1/4"
J17150601V	Plastic	Viton	16 gpm / 60 lpm	8 bar / 115 psi	3/4"	1/4"
J17151200V	Aluminium	Viton	20 gpm / 90 lpm	8 bar / 115 psi	1"	1/4"
J17151200N	Aluminium	Nitrile	20 gpm / 90 lpm	8 bar / 115 psi	1"	1/4"



## Diaphragm Pump Wall Mounting Bracket

J17910010

Wall mounting bracket for all Lubeworks air operated diaphragm pumps.



For up to date information and prices please visit - [www.redashe.com](http://www.redashe.com)