

# ZSBG Safety Blow Guns

A unique range of safety blow guns that offer maximum blowing force with minimal air consumption.

**FEATURES:**

- Impact and weather resistant body
- Corrosion resistant stainless steel nozzle and parts
- Ergonomic design with soft rubber grip that helps eliminate the risk of carpal tunnel syndrome
- Brass threaded air inlet ensures that threads do not shear with repeated use
- Variable speed trigger for full control of amount of air dispensed
- Silent operation with noise level under 80db.  
Conforms to OSHA STD 1910-95 (b) for max. Noise level when used with air with 6 bar (90 PSI) pressure
- Confirms to OSHA STD 1-13.1 for safety and are classified as safety blow guns
- Operating pressure 3.5 bar to 16 bar (50 PSI to 235 PSI)
- Operating temperature - 10°C to 70°C (14°F to 158°F)
- 1/4" BSPF Brass Inlet Thread



**TECHNICAL DATA**

Part No.	Description	Noise level at 100 PSI	Blowing force at 100 PSI	Air consumption at 100 PSI
ZSBG1	Air blow gun with snub nose rubber tip (OSHA ok)	77db	0.26kgs / 0.57lbs	15.89 CFM
ZSBG2	Air blow gun with stainless steel nozzle (OSHA ok)	80db	0.35kgs / 0.76lbs	15.18 CFM
ZSBG3	Air blow gun with stainless steel nozzle and silencer (OSHA ok)	75db	0.31kgs / 0.68lbs	13.42 CFM