

PR Series Portable Hose Reels

PR series trolley mounted reels are constructed from heavy gauge powder coated steel and allow you to move heavy long lengths of hose from one site to another with minimum effort. All swivel joints are 90 degrees and the fluid path will handle product temperatures from -28°C to +107°C

FEATURES:

- All steel heavy duty construction
- A positive steel lock pin - prevents drum from turning when in transit
- Rewind hand crank: Solid steel with a roller hand grip
- Solid 8" rubber tyres
- Steel legs with rubber feet - prevents reel from slipping forward when pulling out hose
- Adjustable drag brake - prevents hose backlash when unreeling
- Supplied as bare reel, hose available at extra cost (Application required).
- Stainless steel plumbing available on request

Rewind: Hand crank - Hand crank attaches to axle and is permanent. The handle maybe removed for flushing out purposes. NB. The handle would not under normal circumstances be removed when the reel is under pressure. Doing so will open the flow path and potentially harm the operator.

Model reference	Hose capacity			Max PSI	Swivel in/out	Size index
	I.D.	O.D.	Feet/M			
PRL-4-100	1/2"	7/8"	100/30m	3000	1/2" x 1/2" BSPF	1
PRL-4-200	1/2"	7/8"	200/60m	3000	1/2" x 1/2" BSPF	2
PRL-5-50	3/4"	1 1/8"	50/15m	3000	3/4" x 3/4" BSPF	1
PRL-6-100	1"	1 1/2"	100/30m	3000	1" x 1" NPTF	3
PRL-6-150	1"	1 1/2"	150/45m	3000	1" x 1" NPTF	4
PRL-1185-1524	1 1/2"	2 1/16"	75/23m	600	1 1/2" x 1 1/2" NPTF	5



Size index	W	H	D	Weight (bare reel & cart)
	Inc handle	Inc cart	Inc cart	
1	933	552	527	23 kgs
2	933	705	527	24 kgs
3	1010	629	699	38 kgs
4	1010	832	699	41 kgs
5	1010	984	699	44 kgs