

Pure Flo Hose Reels

Redashe Pure Flo hose reels safely and efficiently manage, protect and store costly breathing air or food quality hose. Guard against the dangers associated with tangled hose that can lead to trips and kinks that have potential for disaster. Pure Flo hose reels are the perfect solution to the challenge of managing hoses. Offered in spring rewind, hand crank, and motorized retraction, all Pure Flo hose reels come standard equipped with stainless steel air paths and stainless steel swivels with food quality grease, ensuring clean, non-contaminated transfer of products.



For up to date information and prices please visit - www.redashe.com

BENEFITS:

- Store hose safely and efficiently
- Increased operator safety by eliminating tangles, kinks, trips, and falls that result from non-use
- Preserve and extend the life of your costly hose and equipment

FEATURES:

- For low pressure and high pressure breathing air
- Available in hand crank, motorised or spring rewind retraction
- Coxreels' quality solid steel construction
- Durable electrostatic powder coat finish
- Stainless steel reels available

Pure Flo EZ-Coil Hose Reels

Hose reels equipped with the patented EZ-Coil™ results in a controlled retraction, increasing user safety and extending the life of your hose, hose reel and it's components.

FEATURES:

- Stainless steel flow path
- Heavy duty, solid steel construction
- Full flow 90° stainless steel swivel with food quality grease
- 8-position locking ratchet
- Heavy duty, solid steel construction.
- Powder coated blue

Supplied as bare reel, hose available at extra cost (Application needed)



LOW PRESSURE

Model (less hose)	I.D.	O.D.	Hose length (m)	PSI	Width (mm)	Height (mm)	Depth (mm)	Approx. (Lbs.)
EZ-PP-LPL-350	3/8"	21/32"	15	300	156	464	337	23 kg
EP-PP-SHL-3100	3/8"	21/32"	30	300	235	648	584	37 kg

HIGH PRESSURE

Model (less hose)	I.D.	O.D.	Hose length (m)	PSI	Width (mm)	Height (mm)	Depth (mm)	Approx. (Lbs.)
EZ-PP-HPL-350	3/8"	21/32"	15	6000	156	464	337	23 kg
EP-PP-HPL-3100	3/8"	21/32"	30	6000	235	648	584	37 kg