

SP High Capacity Spring Rewind Hose Reels

SP high capacity reels are designed for high volume delivery of air, water and oil at low and medium pressures. Constructed in heavy gauge powder coated steel, SP reels are suitable for fixed applications or on mobile service vehicles where longer lengths or larger diameters of hose are necessary but the convenience of spring rewind is still required. The roller guide can be set for floor, wall or overhead installation.

FEATURES:

- Double supported steel axle ■ Stainless steel roller guides reduce hose wear
- Reinforced steel frame for maximum stability ■ Latching of hose at any length
- Externally mounted full flow swivel for maximum product delivery ■ Supplied as bare reel, hose available at extra cost (Application required). ■ Supplied with mild steel plumbing, stainless steel plumbing on request



Model reference	Hose capacity			Max PSI	Swivel in/out	Size index
	I.D.	O.D.	Length (m)			
SLPL-575	3/4"	1 1/4"	22.5	300	3/4" BSPF	2
SLPL-5100	3/4"	1 1/4"	30	300	3/4" BSPF	2
SLPL-650	1"	1 1/2"	15	300	1" NPTF	3
SLPL-675	1"	1 1/2"	22.5	300	1" NPTF	4
SLPL-725	1 1/4"	1 13/16"	8	250	1 1/2" NPTF	5
SLPL-750	1 1/4"	1 13/16"	15	250	1 1/2" NPTF	6
SLPL-825	1 1/2"	2 1/16"	8	250	1 1/2" NPTF	5
SLPL-835	1 1/2"	2 1/16"	10.5	250	1 1/2" NPTF	7
SLPL-850	1 1/2"	2 1/16"	15	250	1 1/2" NPTF	8
SMPL-575	3/4"	1 1/4"	22.5	3000	3/4" BSPF	2
SMPL-5100	3/4"	1 1/4"	30	3000	3/4" BSPF	2
SMPL-625	1"	1 1/2"	8	3000	1" NPTF	3
SMPL-650	1"	1 1/2"	15	3000	1" NPTF	3
SMPL-675	1"	1 1/2"	22.5	3000	1" NPTF	4

Please call for the available hose options

Size index	Reel dimensions (mm)			Approx weight less hose
	W	H	D	
1	521	521	572	41 kg
2	508	622	660	57 kg
3	533	521	648	50 kg
4	533	724	762	67 kg
5	330	622	660	50 kg
6	330	724	762	56 kg
7	330	724	762	58 kg
8	508	724	762	63 kg