

Top Loading Parts Cleaners

Redashe top loading parts cleaners are designed to free up technicians from washing dirty greasy parts by hand, simply place the part to be cleaned in the basket close the lid turn it on and walk away, allowing other tasks to be carried out, the units are designed to work with a wide range of aqueous cleaning solutions and has a built in heating element which allows the fluid to be heated.

Manufactured from 304 stainless steel the units are robust and built to last.

We maximise the tank capacity to ensure that the fluid has an extended life and doesn't need changing too frequently, if the optional oil skimmer is added to the unit the fluid life can be extended even further, the spray nozzles are simply unscrewed so making the units easy to maintain.

FEATURES:

- 304 stainless steel construction
- Large fluid tank
- 750 and above motorised basket
- Stainless spray bars
- Level control to protect pump and heating element
- Adjustable cleaning time 0 -30 mins.
- Optional extras
- Oil skimmer
- Mobility wheels
- Temperature control 0 - 60
- Easy servicing
- Ventilation point
- Insulation
- Extraction
- Air blow off gun



Redashe

	WASHER 60	WASHER 750 E POWER	WASHER 900 E POWER	WASHER 1150 E POWER	WASHER 1500 E POWER	WASHER 1800 E POWER
Part number	J40014.1	J40016.1	J40010.1	J4009.1	J40011.1	J40015.1
Depth	790 mm	955 mm	1105 mm	1355 mm	1600 mm	2000 mm
Width	940 mm	1035 mm	1185 mm	1470 mm	1850 mm	2300 mm
Height	930 mm	1130 mm	1170 mm	1320 mm	1320 mm	1350 mm
Tank capacity	75 L	90 L	130 L	210 L	250 L	270 L
Weight	65 kg	150 kg	180 kg	210 kg	250 kg	500 kg
Supply	230 V (1~)	400 V (3~)	400 V (3~)	400 V (3~)	400 V (3~)	400 V (3~)
Pump power	0.75 kW	1.85 kW	1.85 kW	2.2 kW	3 kW	6+6 kW
Heating element	2 kW	4.5 kW	6 kW	6 + 3 kW	6 + 3 kW	0-85°C
Max. power	3 kW	7 kW	8.5 kW	12 kW	12 kW	17.5 kW
Temperature	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C	0 - 60°C
Basket diameter	600 mm	740 mm	890 mm	1140 mm	1460 mm	1800 mm
Working height	350 mm	450 mm	450 mm	550 mm	550 mm	550 mm
Load capacity	100 kg	400 kg	400 kg	400 kg	400 kg	400 kg
Pump flow rate	80 L/min	130 L/min	130 L/min	150 L/min	150 L/min	2 x 150 L/min
Pump pressure	2.5 bar	3.5 bar	3.5 bar	4.5 bar	5.5 bar	2 x 4.5 bar
Number of nozzels	30	40	46	64	70	70
Motor driven basket	No	Yes	Yes	Yes	Yes	Yes
Visual fluid level indicator	No	Yes	Yes	Yes	Yes	Yes

Optional extras oil skimmer, wheels, insulation, extraction and air gun.