

R3600-SS Gun Cleaner

FOR SOLVENT BASED PAINTS

The R3600-SS Gun Cleaner is a semi automatic unit that works in two stages. The enclosed automatic wash runs for two minutes using recirculating solvent, washing guns internally and externally. The gun is then rinsed manually with clean solvent spray. A compact design for restricted space operation.

FEATURES:

- Semi automatic
- Spray-out facility
- Sagola, Devilbis, Iwata and SATA approved
- Clean rinse
- Fume extraction*
- Fully enclosed
- 1 or 2 gun versions
- Stainless steel bowl
- Air purge line

* 0.5m³ extraction per second away from the face is recommended by Redashe (HSG258).

TECHNICAL DATA

Working pressure: 75-180 psi (5-12 bar)
Air consumption: 9 c.f.m.
Extraction capacity: 140m³/h (82 c.f.m.) with 15m (49ft) extraction duct
180m³/h (106 c.f.m.) with 5m (16ft) extraction duct
Extractor Diameter: 125mm (5")
Dimensions: Height 880mm Diameter 645mm

LIFE TIME WARRANTY

All Redashe spray gun cleaner pumps carry a lifetime guarantee against faulty materials and workmanship, this guarantee does not apply to fair wear and tear or damage caused by misuse or abuse of the product. Warranty limited to the original installation. This is for all spray gun cleaners pages 166-176 (excludes QuickRinse).

