

C Dual Spring Rewind Hose Reels

Redashe C dual hose reels feature two heavy duty spring rewind hose reels on a single support post. Each reel operates independently for delivery of air or water, oil, grease etc. Finished in a durable powder coated paint to resist corrosion. C reels are ideal for twin service applications at one location reducing installation time and maximising use of available space. Both reels feature multi-position roller arms and latching of hose with fully automatic spring rewind. Swivels and spring cans are externally mounted for ease of access for servicing.

FEATURES:

- Independent operation of each reel
- Heavy duty steel construction with durable blue powder coat finish
- Heavy duty 1/4" plate steel support post
- Twin solid 1" steel axles
- Multi-position roller guide arm
- Non-snap roller guides
- Latching of hose at any length
- Fully automatic hose rewind
- Full flow swivels for maximum product delivery
- Twin 1" oil-lite self-lubricating bearings
- Supplied as bare reel, Hose available at extra cost (Application required)



Model reference	Hose capacity			Max PSI	Swivel in/out	Size index
	I.D.	O.D.	Length (m)			
C-LPL-325-325	3/8"	5/8"	2 x 8	300	3/8" BSPF	1
C-LPL-350-350	3/8"	5/8"	2 x 15	300	3/8" BSPF	1
C-LPL-425-425	1/2"	7/8"	2 x 8	300	1/2" BSPF	1
C-MPL-335-335	3/8"	5/8"	2 x 10.5	3000	3/8" BSPF	3
C-MPL-430-430	1/2"	3/4"	2 x 9	2500	1/2" BSPF	3
C-HPL-135-135	1/4"	17/32"	2 x 10.5	5000	1/4" BSPF	3
C-HPL-330-330	3/8"	43/64"	2 x 9	4000	3/8" BSPF	3

Please call for the available hose options

Size index	Reel dimensions (mm)			Approx weight less hose
	W	H	D	
1	279	457	432	29 kg
3	318	464	438	31 kg