

Large Capacity Hand Crank Dual Hose Welding Reels

The 1275W-C series reels are designed for a higher capacity twin hose oxy-acetylene and oxy-propane gas applications. This bevelled gear hand cranked design has a detachable handle for tidy and compact storage. The robust powder coated steel construction combines maximum stability with ease of use while the dual ported swivel features multiple 'O' rings for positive gas separation.

FEATURES:

- Applications include MAPP gas, propane and natural gas
- Brass swivels as standard with $\frac{3}{8}$ " right and left handed weld fittings
- Easily wraps, stores and protects hose improving workplace safety
- One piece welded steel "A" frame construction
- Self aligning pillow block precision bearings ensure smooth rotation
- Heavy ribbed steel discs with rolled edges for maximum strength and safety
- Long handled lock pin secures reel and prevents rotation when not in use
- Low profile outlet riser and open drum slot design for even wraps of hose around the drum
- Corrosion resistant adjustable tension brake prevents hose backlash when unreeling
- Supplied as bare reel, hose available at extra cost



Model reference	Hose capacity			Max PSI	Swivel in/out	Size index
	I.D.	O.D.	Length (m)			
1275WL-3-100	$\frac{3}{8}$ "	$1\frac{1}{16}$ "	30	200	$\frac{3}{8}$ " BSPF	1
1275WL-3-150	$\frac{3}{8}$ "	$1\frac{1}{16}$ "	45	200	$\frac{3}{8}$ " BSPF	2
1275WL-3-250	$\frac{3}{8}$ "	$1\frac{1}{16}$ "	75	200	$\frac{3}{8}$ " BSPF	3
1275WL-3-350	$\frac{3}{8}$ "	$1\frac{1}{16}$ "	106.5	200	$\frac{3}{8}$ " BSPF	4

See price list for hose options available on these reels

Size index	Reel dimensions (mm)			Approx weight less hose
	W	H	D	
1	479	460	603	21 kg
2	581	460	603	22 kg
3	733	460	603	26 kg
4	886	460	603	29 kg