Heavy Duty Spring Rewind Reels

FEATURES:

- Heavy duty steel construction with durable blue powder finish
- Double supported solid 1" steel axle
- Multi-position roller arm gives full range of mounting options
- Four way, non-snag roller guides to reduce hose wear
- 1/4" steel mounting base for maximum stability
- Slotted and drilled mounting holes for easy installation
- Latching of hose at any length
- Fully automatic hose rewind for neat and tidy storage
- Externally mounted full flow swivel for maximum product delivery
- Supplied as bare reel, hose available at extra cost (Application required).

P-LP/SH Heavy Duty Spring Rewind Reels

Model reference	Hose capacity			Max PSI	Swivel in/out	Size index
	I.D.	O.D.	Length (m)			
P-LPL-125	1/4"	1/2"	8	300	1/4" BSPF	1
P-LPL-150	1/4"	1/2"	15	300	1/4" BSPF	2
P-LPL-325	3/8"	5/8"	8	300	3/8" BSPF	1
P-LPL-350	3/8"	5/8"	15	300	3/8" BSPF	2
SHL-N-375	3/8"	5/8"	22.5	300	3/8" BSPF	4
SHL-N-3100	3/8"	5/8"	30	300	3/8" BSPF	4
P-LPL-425	1/2"	7/8"	8	300	1/2" BSPF	2
SHL-N-450	1/2"	7/8"	15	300	1/2" BSPF	3
SHL-N-475	1/2"	7/8"	22.5	300	1/2" BSPF	4
SHL-N-4100	1/2"	7/8"	30	300	1/2" BSPF	4
SHL-N-525	3/4"	1 1/8"	8	300	3/4" BSPF	3
SHL-N-550	3/4"	1 1/8"	15	300	3/4" BSPF	4
SHL-N-575	3/4"	1 1/8"	22.5	300	3/4" BSPF	6
SHL-N-635	1"	1 7/16"	10.5	300	1" NPTF	5
SHL-N-650	1"	1 1/2"	15	300	1" NPTF	6
Please call for the available hose options						

Coxreel series P-LP/SH heavy duty hose reels are engineered for rugged durability. Constructed in 'heavy gauge' powder coated steel for maximum strength and reliability, these spring rewind reels provide years of trouble free service with minimum maintenance. The multi-position roller arm adjusts for wall, overhead and floor mounting options, while the full flow swivel ensures maximum product delivery. All models available with or without fitted hose.

Size index	Reel dimensions (mm)			Approx weight less hose
	W	H	D	
1	152	368	349	11 kg
2	156	464	438	18 kg
3	235	533	498	25 kg
4	235	648	584	37 kg
5	254	648	584	32 kg
6	318	648	610	34-35 kg

P-MP/MP/P-HP/HP Heavy Duty Spring Rewind Reels

Model reference	Hose capacity			Max PSI	Swivel in/out	Size index
	I.D.	O.D.	Length (m)			
P-MPL-325	3/8"	5/8"	8	3000	3/8" BSPF	1
MPL-N-350	3/8"	5/8"	15	3000	3/8" BSPF	2
MPL-N-375	3/8"	5/8"	22.5	3000	3/8" BSPF	3
MPL-N-3100	3/8"	5/8"	30	3000	3/8" BSPF	3
P-MPL-425	1/2"	3/4"	8	2500	1/2" BSPF	1
MPL-N-450	1/2"	3/4"	15	2500	1/2" BSPF	2
MPL-N-475	1/2"	3/4"	22.5	2500	1/2" BSPF	3
MPL-N-4100	1/2"	3/4"	30	2500	1/2" BSPF	3
P-HPL-125	1/4"	1/2"	8	5000	1/4" BSPF	1
HPL-N-150	1/4"	1/2"	15	5000	1/4" BSPF	2
HPL-N-1100	1/4"	17/32"	30	5000	1/4" BSPF	3
P-HPL-325	3/8"	3/4"	8	4000	3/8" BSPF	1
HPL-N-350	3/8"	3/4"	15	4000	3/8" NPTF	2
Please call for the available hose options						

Designed for medium and high pressure delivery of water, oil and grease these heavy duty reels feature the same design benefits as the P-LP/SH series. The oil and grease models are ideally suited to lubrication systems in automotive workshops where durability and reliability are paramount.

For pressure washer users the 3000 psi / 150 °C rating of the medium pressure water reels provides a solution to the problem of persistent hose damage.

Size index	Reel dimensions (mm)			Approx weight less hose
	W	H	D	
1	178	464	438	19 kg
2	235	533	498	24 kg
3	235	648	584	37 kg