

SS Stainless Steel Spring Rewind Reels

Constructed in heavy gauge 304 stainless steel and other noncorroding materials, Redashe SS hose reels are designed for use in harsh, corrosive environments or where hygiene is of primary importance. They are ideally suited to washdown applications in food processing and chemical manufacturing and should also be specified for offshore and marine applications where salt spray rules out the use of standard powder coated steel models.

FEATURES:

- Heavy duty 304 stainless steel construction on discs and frame
- Double supported solid 1" stainless steel axle
- Latching of hose at any length
- All working parts fully accessible for servicing
- Fully automatic hose rewind for neat and tidy storage
- Multi-position roller arm gives full range of mounting options
- Four way, non-snap roller guides to reduce hose wear
- 1/4" stainless steel mounting base for maximum stability
- Slotted and drilled mounting holes for easy installation
- Externally mounted full flow swivel for maximum product delivery
- Supplied as bare reel, hose available at extra cost (Application needed)



Model reference	Hose capacity			Max PSI	Swivel in/out	Size index
	I.D.	O.D.	Length (m)			
P-LPL-425SS	1/2"	7/8"	8	300	1/2" BSPF	3
SHL-N-350SS	3/8"	5/8"	15	300	3/8" BSPF	2
SHL-N-450SS	1/2"	7/8"	15	300	1/2" BSPF	1
SHL-N-525SS	3/4"	1"	8	300	3/4" BSPF	1
SHL-N-4100SS	1/2"	7/8"	30	300	1/2" BSPF	4
SHL-N-550SS	3/4"	1"	15	300	3/4" BSPF	5
MPL-N-350SS	3/8"	5/8"	15	3000	3/8" BSPF	1

Please call for available hose options

Size index	Reel dimensions (mm)			Approx weight less hose
	W	H	D	
1	235	533	498	21 kg
2	222	533	498	20 kg
3	178	464	445	18 kg
4	248	648	584	37 kg
5	248	648	584	32 kg