

T512 5:1 Oilmaster Ratio Pumps

The T512 Oilmaster® is an air operated 5:1 ratio stub pump that delivers up to 15 litres per minute. This is a very quiet pump that is ideal for all workshops where transfer of lubricating oils over varying distances through hose reels with dispensing nozzles and/or meters is required.

The T512 Oilmaster®, is supplied as a stub pump with a 50mm (2") BSP bung adaptor, and 25mm (1") BSP (F) oil inlet. T512 pump is ideally suited for the Macnaught HG series oil control guns and Retractable hose reels.

FEATURES:

- Stub pump for inclusion in a workshop or mobile bulk oil system
- Suitable for use with oils to SAE 140, automatic transmission fluid
- Delivers up to 15 litres (4 US gal) per minute (at the pump)
- Air inlet 1/4" BSP or NPT (F)
- Oil inlet 1" BSP (F)
- Oil outlet 1/2" BSP (F)
- 50mm (2") adjustable bung adaptor
- Optional ST003AS suction tube available



For up to date information and prices please visit - www.redashe.com

FLOW RATES – T512 OILMASTER

Material	3m (10ft) x 12.5mm (1/2") hose, 10m (33ft) x 12.5mm (1/2") hose reel and delivery gun	9m (29ft) x 2.5mm (1/8") hose, 10m (33ft) x 2.5mm (1/8") hose reel and delivery gun
OIL SAE 10	6.5 ltr (1.7 gal) per min	6 ltr (1.6 gal) per min
OIL SAE 30	5 ltr (1.4 gal) per min	5 ltr (1.4 gal) per min
OIL SAE 90	4 ltr (1.1 gal) per min	3.5 ltr (0.93 gal) per min

Note:

1. Flow rates in litres per minute at 700kPa/100 PSI/7 bar and 23°C.
2. Flow rates are a guide only and the actual output may vary from that stated.
3. Variations in flow rate can result from compressor volume, air pressure, hose construction, hose fittings, ambient conditions and system pipe work.

